



# MEMS Tilt Beam

**MEMS**  
TILT & INCLINATION  
SERIES**RST Instruments Ltd.**11545 Kingston St.,  
Maple Ridge, BC  
Canada V2X 0Z5Telephone: 604 540 1100  
Facsimile: 604 540 1005  
Toll Free: 1 800 665 5599

info@rstinstruments.com

www.rstinstruments.com

**applications**

Monitoring the effects of tunneling and excavating on nearby buildings and other structures.

Monitoring the movement of tunnel walls and railway tracks.

Monitoring the stability of structures where slope instability is occurring.

Monitoring the deflection of bridges and beams under load.

**features**

Simple construction with no moving parts to damage.

Convenient to install on any structure and easy to use.

Beams can be linked together to provide detailed movement data over long distances.

Analog, digital and frequency outputs available.

Easily adaptable to datalogging.

Integral temperature sensor.

Fiberglass composite beams minimize thermal effects.

**accessories**

Terminal stations.

'GeoViewer' Monitoring Software, near real time.

**additional ordering info**

Number of beam modules required.

Horizontal or vertical beam.

Groutable or expansion shell type anchors.

Portable readout or datalogger.

Biaxial versions also available.

RST Instruments Ltd. reserves the right to change specifications without notice.

MEMS Tilt Beams measure differential movements in structures and consist of a MEMS sensor mounted on a rigid, fibreglass beam. The beam is mounted on anchor bolts set into the structure. They can be installed on any structure by joining together lengths of beams and are extremely accurate in generating movement profiles over long distances. Readings are taken with a manual readout by connecting at the end of the single cable linking all the bussed beams, or with a datalogger at a remote monitoring station. Site specific, near-real time monitoring software is available.

**specifications**

ITEM	DESCRIPTION
Range	±15° (other ranges upon request)
Resolution (analog)	±5 arc sec. (±0.025 mm/m) (10Hz BW)
Resolution (digital)	±2 arc sec. (±0.0006°) (0.01 mm/m)
Non-linearity (analog)	±0.05% F.S. (±0.0075°) (0.13 mm/m)
Non-linearity (digital)	±0.0125% F.S. (±0.002°) (0.03 mm/m)
Repeatability (analog)	±0.025% F.S. (±0.004°) (0.06 mm/m)
Repeatability (digital)	±0.0125% F.S. (±0.002°) (0.03 mm/m)
Sensor	MEMS (Micro-Electro-Mechanical Systems) Accelerometer, Uniaxial or Biaxial
Operating Temp.	-40 to 85°C (-40 to 185°F)
<b>FIBREGLASS BEAM (MOUNTING BRACKETS INCL.)</b>	
Beam Dimensions	51 X 51 mm (2 X 2 in.)
Gauge Length	1, 2 or 3 m (3, 5, 10 ft.)

**ordering info**

ITEM	PART #
<b>MEMS HORIZONTAL TILT BEAM MODULE</b>	
Analog Voltage - requires beam	IC6015
4-20mA - requires beam	IC6016
Digital Output - requires beam	IC6017
Digital Bus Output - requires beam	IC6018
Frequency - requires beam	IC6019
<b>MEMS VERTICAL TILT BEAM MODULE</b>	
Analog Voltage - requires beam	IC6080
4-20mA - requires beam	IC6081
Digital Output - requires beam	IC6082
Digital Bus Output - requires beam	IC6083
Frequency - requires beam	IC6084
<b>MEMS BEAMS</b>	
0.5 m - requires a tilt beam module	IC6060
1 m - requires a tilt beam module	IC6061
2 m - requires a tilt beam module	IC6062
3 m - requires a tilt beam module	IC6063

**READOUTS & DATALOGGERS**

MEMS Analog Readout (analog systems)	IC6800-V
Ultra Rugged Field PC (digital bus systems)	IC32000-14803
Digital Interface for Ultra Rugged Field PC with software	ELGL4010

flexDAQ Dataloggers (analog and digital systems)



WORKS WITH

**flexDAQ**  
DATALOGGERS  
custom, turn-key datalogger  
systems shipped "ready to run"