



Carlson Pore Pressure Cells



RST Instruments Ltd.
200 - 2050 Hartley Ave.
Coquitlam, BC
Canada V3K 6W5

Telephone: 604 540 1100
Facsimile: 604 540 1005
Toll Free: 1 800 665 5599



info@rstinstruments.com

www.rstinstruments.com



Water pressure in the pores of a granular material like soil reduces the internal friction and therefore the stability. This pore pressure can be measured by a device which separates the water pressure from the intergranular pressure. In the Carlson Pore Pressure Cell, the water pressure is admitted to an internal diaphragm through a porous disc which holds back the soil or other granular material. The deflection of the internal diaphragm is measured with the same sensing element as is used in the stress meters. For a pore pressure cell to be fully satisfactory, it must permit measurement with a minimum of water movement. Both of these requirements are met by the Carlson Pore Pressure Cell.

operating principle

Carlson Instruments are elastic wire strain meters containing two coils of highly elastic steel wire, one of which increases in length and electrical resistance when a strain occurs, while the other decreases. The ratio of the two resistances is independent of temperature (except for thermal expansion) and therefore the change in resistance ratio is a measure of strain. The total resistance is independent of strain since one coil increases the same amount as the other decreases due to a change in length of the meter. Therefore, the total resistance is a measure of temperature.

applications

Measurement of pore water pressure in soils.

features

Zero displacement.

Integral temperature measurement.

50 year track record and proven Carlson design.



GEOTECHNICAL . MINING . STRUCTURAL



CA80003D



specifications + ordering info

Carlson Pore Pressure Cell



specifications

DESCRIPTION	MODEL P25	MODEL P50	MODEL P100	MODEL P200
Range	25 psi (172 kPa)	50 psi (345 kPa)	100 psi (690 kPa)	200 psi (1379 kPa)
Resolution	0.1 psi (0.7 kPa)	0.2 psi (1.4 kPa)	0.4 psi (2.8 kPa)	0.8 psi (5.5 kPa)
Resolution Temperature	0.1°F (0.05°C)	0.1°F (0.05°C)	0.1°F (0.05°C)	0.1°F (0.05°C)
Weight	1.02 kg (2.25 lbs.)	1.02 kg (2.25 lbs.)	1.02 kg (2.25 lbs.)	1.02 kg (2.25 lbs.)

ordering info

ITEM	PART #
Model P25	CA220A025
Model P50	CA220A050
Model P100	CA220A100
Model P200	CA220A200

cable specs

The cable most commonly used is heavy duty, neoprene rubber-covered, with either three or four conductors. Alternate cable types are available to suit site specific conditions and we invite your inquiries.

The Carlson MA-6B and later series readout instruments, while compatible with both three and four wire systems, require only three conductors to monitor both temperature and resistance. Earlier versions of Carlson readouts require four conductors to monitor both parameters. We recommend that the total design length of cable be attached at the factory in order to assure system integrity. Should the final design length not be known at the time of order, specify the total length of cable to be supplied in bulk, and that a 1 m. (40 in.) length of either three or four conductor be attached. As conductor diameter is determined by lead length, please specify the approximate total length, to insure that the most appropriate cable is supplied.

While field splicing is possible, the instructions in the Carlson field manual must be followed.

accessories

- Portable readout instruments
- Bentonite pellets
- Data loggers
- Cable terminal stations
- Filter fabric installation socks
- Optional armoured cable
- Alternate filter types



GEOTECHNICAL . MINING . STRUCTURAL