



» piezometers

Casagrande Standpipe Piezometer



RST's Casagrande Type Standpipe Piezometer tip consists of a slotted PVC body enclosing and protecting a porous plastic filter element. A CPVC body is available for leachate extraction.

For measurement of water pressures in ground where the time lag and high displacement requirements inherent in standpipes are not crucial, and where the presence of standpipes will not hinder construction. A bubbler system may be incorporated to allow remote reading, Bourdon tube gauges may be attached to monitor artesian pressures.

Drive-in models and custom sizes are also available, contact RST Instruments for more details.

specifications

DESCRIPTION	SPECIFICATION
Maximum O.D.	1.32 in. (3.35 cm)
Filter Area	37.69 sq. in. (243 sq. cm)
Body Material	1 in. PVC
Pore Diameter	70 micron
Permeability	3×10^{-4} m/s (low air entry)

Accepts 1 in., 0.75 in. and 0.5 in. PVC solvent weld riser pipe. Non standard types of riser fittings may be provided on request. Please contact us regarding price and delivery information.

ordering info

SIZE	PART #
5.24 cm (6")	PP0306
30.48 cm (12")	PP0312
45.72 cm (18")	PP0318
60.96 cm (24")	PP0324
Steel Drive Point to fit 12" Casagrande	FIPSP0125

Custom sizes and options are available, contact RST Instruments for more details.

optional equipment

- 1, 0.75, or 0.5 in. riser pipe
- Bentonite pellets
- Protective enclosures
- Bubbler readout systems
- Water level meter



RST Instruments Ltd.
200 - 2050 Hartley Ave.
Coquitlam, BC
Canada V3K 6W5

Telephone: 604 540 1100
Facsimile: 604 540 1005
Toll Free: 1 800 665 5599



info@rstinstruments.com

www.rstinstruments.com

applications

Monitoring of pore pressures in dams and embankments.

Slope stability investigation and leachate extraction.

Groundwater sampling, monitoring, dewatering and drainage operations.

features

The flush body design, permits a 33% larger filter area than 0.75 in. externally coupled instruments, while maintaining the same outside diameter.

A unique two step internal bushing, will accept either 0.5 in. or 0.75 in. riser pipes while the body will accept a 1.0 in. coupling. The same tip, therefore, will fit all three common sizes of risers.

The large number of uniform pores permits high permeability in a short length.

Smooth and protected filter element resists clogging.

Uniform 70 micron porosity.

May be cleaned by back flushing.

Excellent chemical resistance.

Low cost, with same day delivery.

GEOTECHNICAL . MINING . STRUCTURAL



EPB0030H