



# VW2106 Vibrating Wire Readout



VW2106 Vibrating Wire Readout shown with Vibrating Wire Piezometer



The portable VW2106 Vibrating Wire Readout reads, displays, and logs both vibrating wire sensors and thermistors. Vibrating wire load cells can be read without any additional accessories.

Unprecedented accuracy, flexible memory options and ease of use make the VW2106 invaluable for projects requiring vibrating wire sensor monitoring. Maximum download time is only 15 seconds.

Complementing its high level of accuracy, the VW2106 is also designed for maximum efficiency with the user in mind. In addition to the simple power requirements of only 3 "AA" batteries, the VW2106 comes well-equipped with standard features such as a large graphics display with backlight, a built-in multiplexer, "no-tools" vibrating wire transducer inputs (eliminating the need for alligator clips), and a convenient on-board speaker for sensor diagnostics.

## specs

DESCRIPTION	SPECIFICATION
Vibrating Wire Readout Excitation Range	400 Hz to 6000 Hz, 5 V Square Wave
Vibrating Wire Readout Resolution	0.01 $\mu$ s
Vibrating Wire Readout Timebase Accuracy	$\pm$ 50 ppm
Supported Temperature Readout Sensors	NTC3000 (standard), NTC2252, NTC10K, RTD
Temperature Readout Accuracy	$\pm$ 0.1°C
Temperature Readout Range	-50°C to 80°C
Display	Graphic 128 x 64 pixels large character display
Display Backlight	High efficiency LCD with auto off
Max Instrument Locations	254
Memory Capacity	11,400 custom labelled points
Location Identification String	Up to 20 characters
Download Speed	15 seconds (full memory)
Battery	3 "AA" alkaline
Battery Indicator	On-screen, low battery indicator
Operating Temperature	-20°C to 60°C
Dimensions	W 22 cm x D 19 cm x H 9.5 cm (8.75 x 7.5 x 3.75in.)
Weight	1.1 kg (2.4 lbs)

## ordering info

PART #	DESCRIPTION
VW2106	Vibrating Wire Readout



**RST Instruments Ltd.**  
200 - 2050 Hartley Ave.  
Coquitlam, BC  
Canada V3K 6W5

Telephone: 604 540 1100  
Facsimile: 604 540 1005  
Toll Free: 1 800 665 5599



info@rstinstruments.com

www.rstinstruments.com

## applications

Reads, displays, and logs both vibrating wire sensors and thermistors.

## features

Durable, compact design for excellent portability and field use.

Large graphics display with a convenient backlight.

Readings in raw or engineering units.

Built-in multiplexer for load cells up to 6 vibrating wire gauges.

"No-tools" vibrating wire transducer inputs eliminates the need for alligator clips.

Field-replaceable "AA" alkaline batteries eliminate the need for a large, bulky 12 V battery and a charger.

On-board speaker for sensor diagnostics.

Stores up to 254 instrument locations per route, each with a text label, calibration constants, previous data, and up to 11,400 time/date stamped data points.

Data transfer to a host computer via USB in a compatible file format for Microsoft Excel® and other spreadsheets. User friendly host software for Microsoft Windows® included.